

Fuel Scout Solo



Smaller version of Fuel Scout Plus
Perfect for use in confined spaces
Wall-mounted or in tank cabinet
Same functions as Fuel Scout Plus
IP65 Weatherproof

The Fuel Scout Solo is a smaller version of our state-of-the-art fuel management system, a perfect for use in confined spaces. Can be used as a standalone wall-mounted option, or within the end of a tank enclosure.

Using a programmable contactless electronic tag, users can simply offer the tag to the control panel, enter a PIN or ID and odometer (if required) and begin dispensing fuel within seconds. The system is extremely flexible, capable of being programmed to be as accessible or secure as your needs require.

The Fuel Scout Solo is capable of multiple fuelling modes to suit any fleet management need. Tags are programmable at the Fuel Scout Plus with the manager's key, or at your office using the optional Desktop programmer unit.

Data capture is simple, with all extracted report data automatically backed-up to ensure the highest level of data integrity. Concise and simple reporting to Microsoft Excel™ provides performance feedback and chart analysis.

FUEL MANAGEMENT



Fuel Scout Solo

Specification

- › Large graphic LCD display providing clear operating instructions
- › Robust contactless RF TAG fuelling operation
- › Alphanumeric entry via front panel to enable flexible data capture
- › Multiple data transfer and retrieval options: USB, LAN, RS485, modem & GSM
- › Microsoft Windows compatible
- › Wall mounted cabinet
- › Uniquely coded door access key – access to pump override
- › Rugged membrane front panel with scratchproof display window
- › Weather resistant to IP65 standard
- › Pulse input interfaces 100PPL or 10PPL
- › Pulser: Closed contact, less than 600 ohms
- › Active pulser: Open collector output
- › Active pulser voltage: 5v @ 1amp
- › 230v AC @ 50Hz – less than 30 watts (110v available on request)
- › Voltage tolerance of +/- 30 volts
- › 6amp fuse/breaker (standalone)
- › Maximum number of tags: 65,000
- › Max number of pumps: 4 per Fuel Scout
- › Transaction capacity: 200,000
- › Non-volatile memory: 32MB
- › USB download as standard

Options

- › PC cable link
- › Modem kit via landline
- › GSM modem kit
- › Stainless steel cabinet
- › Programmed data tags
- › Data key panel option
- › Programmed data key
- › Desk Top Data Tag or Data Key Programmer
- › Software for Tank Gauging interface
- › PC software (windows 98 to windows 8)
- › Pump mount plate
- › Connection to ATG (tank gauges)

Dimensions

- › 400mm (H) x 400mm (W) x 200mm (D)

FUEL MANAGEMENT



Fuel Scout Solo

Product codes

Part no	Description
PFSP-SOLO-USB	Fuel Scout Solo USB in Wall Cabinet
PFSP-SOLO-MO	Fuel Scout Solo with Modem Kit via landline
PFSP-SOLO-GSM	Fuel Scout Solo with GSM Modem Kit in Wall Cabinet
PFSP-SOLO-LAN	Fuel Scout Solo with LAN Modem Kit in Wall Cabinet
PFSP-SOLO-CABLE	Fuel Scout Solo Cable Link to PC USB in Wall Cabinet

Accessories

ZFSTAG	Programmed Data Tags – each
ZFSKEYMKB	Data Key panel option
ZFSDATAKEY	Programmed Data Key – each
ZFSTAGPROGR	FS Desk Top Tag Programmer Unit including Software
ZFSKEYPROGR	FS Desk Top Key Programmer Unit including Software
ZFSSOFTWARE 6	Software for Tank Gauging interface