

ZEON

## Zeon Commercial Fleet 110 LPM ATEX Approved



Zeon Mono Fleet solution with twin hose

ATEX approved for Diesel

Complies to ATEX IIA T3

Manufactured to EN 13617-1

Capable of withstanding harsh environments

Ideal for budget-conscious commercial operators

Mono unit with twin hose

Diesel, Gas Oil and Biodiesel

0.25% meter accuracy

Stainless steel construction

Compatible with fuel management systems

The Zeon Commercial high speed pump is Pumptronics' low-cost solution for fleet operators looking to install a hard-working, reliable commercial pump with a standard nozzle and dry break nozzle for bus operators

Thanks to its spill-free refuelling system, the Zeon Fleet range reduces fuelling time and provides a reduction in the cost associated with wasted fuel from spillages. Crucially, it keeps operators and the working environment clean and safe, and eliminates the threat of theft as the nozzle has to be connected to the vehicle in order to dispense fuel.

Though we have designed this to offer a low-cost approach to fuelling, quality has not been compromised in any way,

The Zeon range is manufactured to the latest hazardous requirements for Diesel fuels, ATEX approved for the latest Diesel zoning, complies with ATEX IIA T3 and manufactured to EN13617-1.

The Zeon range utilises a stainless steel chassis design, meaning you can rely on it to withstand the toughest of

Environments and represents a solid, reliable rugged solution for the commercial environment where cost are an important consideration.

Zeon's compact size makes it ideal for locating within the end cabinet of the bundled area of a tank pack.

Crucially it can be linked to a variety of fuel management systems, and with its accuracy provides the ability for effective stock reconciliation and ultimate control.

## ZEON



# Zeon Commercial High Speed 110 LPM ATEX Approved

### Specification

- › Stainless steel construction
- › 110 LPM
- › ATEX approved for Diesel Fuels.
- › Manufactured to EN13617-1
- o Certificate number CML 15ATEX9092X
- › Pumping unit with full air separation (not available in dispenser format)
- › Meter accuracy of 0.25%
- › Twin solenoids to ensure only one nozzle in use at a time.
- › Electronic head enclosure with illuminated volume display, one side only
- › Integral nozzle locking
- › Dry break nozzle and Std Latched nozzle.
- › 3.3m hose as standard, other lengths are available.
- › Pulse output interfaces 100PPL or 10PPL for fuel management systems.
- › Not approved for resale
- › 12 months warranty

### Options

- › Optional Second side display available
- › High hose
- › Matching stainless under pump plinths for sites without suitable islands
- › Galvanised Under pump cradles/stools for new installations
- › Breakaway hose coupling

### Dimensions

- › 1150mm (H) x 540mm (W) x 450mm (D) – Weight: 140kg

### Checklist

- ✓ Diesel Only
- ✓ Electronic

## ZEON



# Zeon Commercial High Speed 110 LPM

### Product codes

Part no	Description
ZE110SOB-F	Zeon 110LPM – Fleet Mono – Twin Hose

### Accessories

ZEDIS001	Second Side Volume Only Display
ZESB90	1" Breakaway & Pigtail 90 LPM
HHOSE	Stainless Steel High Hose Option – Per Hose
Three phase 2	Three Phase Motor Option
NC002081	GRP Mono Under Pump Sump